


Outline

- Large Liquid Scintillator Detectors (LLSD) overview: performance, usage, advantages and disadvantages
 - Caveat: Focus on monolithic detectors → Will skip segmented detectors (NOVA 14 kton LS)
- KamLAND/KamLAND-Zen instrumentation and scientific journey
- Brief comment on Borexino and SNO+
- Skip JUNO as the focus is more on the experience of the current generation





Summary


Large Liquid Scintillator Detectors (LLSD)


- A very privileged club: detector volume measured in 100s of tons of liquid scintillator (LS)
- Multiple applications: neutrinoless double beta decay (NDBD), neutrino oscillations, neutrino mass ordering, solar physics, sterile neutrino search, geoneutrinos for geology

Use: reactor vs, solar vs, geo vs, source vs, supernovae vs









Borexino/SOX SNO+
J. Maricic, Large Liquid Scintillator Detectors

Performance of LLSDs

- Calorimetric detectors full energy containment allows:
 - Full spectral fit
 - Vertex reconstruction
 - No escape or invisible energy of β , $\gamma \rightarrow$ background identification relatively easy



- Significant self-shielding from external gamma-rays and neutrons
 - LS is hydrogen reach excellent at stopping and capturing both fast and radiogenic neutrons attractive veto for DM hunting
- LS is intrinsically radio pure → further purification by distillation (demonstrated to work)
- Minimal detector material \rightarrow example: ~25µm thick nylon film holding LS
- Straightforward scalability of target volume in case of NDBD
- **BUT**: relatively poor energy resolution (few percent) → can be improved
 - Addressed by higher PPO concentration in LS, greater photodetector coverage, higher quantum efficiency for PMTs and light concentrators.




March,2016


KamLAND/KamLAND-Zen Instrumentation and Scientific Journey

KamLAND Detector Scheme


- 1kton of LS surrounded by buffer oil and acrylic Rn barrier.
- 1325 17" PMTs
- 554 20" PMTs
- 34% photocatode coverage
- 225 20" PMTs veto water Cherenkov detector
- 300 p.e./MeV observed at the center.
- *Outstanding LS radiopurity:

$$\begin{array}{lll} U & (3.5 + 0.5) \text{ x } 10^{\text{-}18} \text{ g/g} \\ \text{Th} & (5.2 + 0.8) \text{ x } 10^{\text{-}17} \text{ g/g} \\ \text{K} & < 2.7 \text{ x } 10^{\text{-}16} \text{ g/g} \\ \end{array}$$







KamLAND Neutrino Oscillation and Geoneutrino Results



Neutrinos from reactors around Japan



⁷Be solar v measured With well understood backgrounds




Toward ⁷Be solar neutrino measurement

• When the first internal analysis of geoneutrinos was launched, a large signal was

observed → way above Earth model predictions

- New background was identified
- LS was contaminated with ²¹⁰Pb, daughter of ²²²Rn, part of the ²³⁸U chain
- Concentration of ²²²Rn in mine air 10 times higher than outside
- This was also a serious background for ⁷Be solar neutrino measurement




Anti-neutrino energy, E. (MeV)

Purification campaigns to reduce ²¹⁰Pb and other contaminants 2007 - 2008



- 2 distillation campaigns to remove ²¹⁰Pb
- Included N₂ purge to remove ⁸⁵Kr and ³⁹Ar




Purified scintillator

LS is distilled into MO, PC and PPO, remixed an purged with N₂.


Purification campaign results

- The first campaign (2007) less successful due to some mixing of unpurified and purified LS
- In the second campaign: strict control of LS density and temperature
- Total circulation: 5.6 times full volume = 1669 m³ (campaign I) + 4856 m³ (campaign II)



KamLAND-Zen – NDBD Experiment Retrofitting detector for rare event search


Neutrinoless Double Beta Decay



- Second order process.
- Half life has been observed for several nuclei.

- Forbidden in the Standard Model (<u>lepton number violation</u>)
- Its observation would constitute proof

KamLAND-Zen: NDBD with ¹³⁶Xe



- Operational detector
 - → relatively low cost: ¹³⁶Xe + mini-balloon (MB)
 - & quick start: '09 (funding received) '11 (KZ start)
- LLSD + clean → negligible external gammas Only needs very clean Xe and and MB
- Xe-LS easily purified and MB replaceable as needed
 - → straightforward scalability to several tons of Xe
- Background cross-check by running in different conditions with enriched Xe, no Xe (dummy LS)
- No escape or invisible energy from β , γ
 - → BG identification fairly simple
- Continued detection of geoneutrinos with Japanese reactors off. J. Maricic, Large Liquid Scintillator Detectors

Balloon Production and Installation




- MB: mechanical strength, Xe barrier (<1kg/yr)
- Nylon film OK (EVOH not strong enough)
- Minimizing backgrounds:
 - MB made with thin and clean film
- Balloon first filled with dummy LS
- Then dummy LS replaced with Xe LS





Balloon Installed



Minimum inactive detector material: 25 µm thin balloon film. Backgrounds on balloon surface are of great concern.

Balloon produced in very clean conditions.

Brand new LS used to load with Xe.

Xe distillation as well.


KamLAND-Zen Phase I – 89.5 kg yr

 Balloon deployed and filled Xe loaded LS in 2011

```
Xenon loaded LS (Xe-LS)
decane 82%
pseudo-cumene 18%
PPO 2.7 g/liter
xenon 2.44 wt%
```

$\sigma_{E}(2.5\text{MeV}) = 4\%$


 An unexpected background found dominating 0vββ region




 $T^{0v}_{1/2} > 1.9 \times 10^{25} \text{ yr (90\% C.L.)}$


Source of Unexpected Background


- Background traced back to Fukushima accident fallout from the accident introduced ^{110m}Ag in March 2011, at the time of MB construction.
- No escape β , γ background spectrum shape fitting made easy






- Consistent with 110m Ag (Q = 3.01 MeV, $T_{1/2}$ = 260 days)
- Purification of Xe loaded LS necessary






What about other backgrounds?

▶¹0C from muon spallation




- Throughout volume
- 3 fold-coincidence
- Dead-time free electronics



- ① muon (>100MeV) ↓ 207 µsec ② neutron capture
- (~2.2 MeV)
- ③ ¹⁰C decay (1.5 ~ 3.5 MeV)

s ▶²¹⁴Bi background tagging



²¹⁴Bi/²¹⁴Po delayed coincidence

Transparent efficiency of α particle from ²¹⁴Po decay is important for Tag(1).


Thin film is better.

Tag² ²¹⁴Pb/²¹⁴Bi event

Tag② uses vertex correlation between ²¹⁴Pb and ²¹⁴Bi event Control accidental coincidence is important. Reduce ⁴⁰K contamination in film.

- MB surface background
- Fine volume binning


 $\tau = 207$



Phase-2 380 kg

After purification

^{110m}Ag reduction < 1/10




2013/12/11 – 2014/10/27 534.5 days (504 kg-yr)

IN-SITU
PURIFICATION
POSSIBLE!


Further Improvement of Sensitivity

- To reduce backgrounds from MB film contamination all volume, time-binned analysis
- 40 equal volume bins! Radial cut: R < 1 m
- Source calibration at the end of the run to determine energy and vertex resolution




Energy and radial distribution well reproduced by known backgrounds.

use FV for period-2 data upper hemisphere R<1.26 m (5 bins) lower hemisphere R<1.06 m (3 bins)




Final Combined KamLAND-Zen 1&2 phase result



$$T_{1/2}^{0\nu} > 1.07 \times 10^{26} \,\mathrm{yr}$$


 $\langle m_{\beta\beta} \rangle < (61 - 165) \,\mathrm{meV}$



- The best limit overall!
- Getting closer to Inverted Hierarchy region!

Next phase: KamLAND-Zen 800

- The MB has been removed in December 2015 →
 - → all Xe recovered during recirculation and MB deflation (for tank inspection required by law)



- Search with 750 kg of enriched Xe → improve sensitivity to better than 50 mV.
- Reduce film background due to dust → fabricated new, cleaner and larger balloon
- Further optimize ¹⁰C triple-fold coincidence
- Nothing can be done about 2v background without further improving energy resolution (planned for KamLAND-II)

Example of improvements

before after









keep staying away goggle welding machine cover sheet. glove on glove laundry twice a day. clean underwear.

changing room in a clean room . dust visualization

more neutralizer sheets ricic, Large Liquid Scintillator Detectors




2nd MB fabrication Cleaning a lot With improvements...

We confirmed that the mini-balloon is cleaner!!

Measures we took worked!

2nd MB deployed in August 2016


At the same time, we noticed;







- camera image
- load cell
- balloon shape reconstruction with ²¹⁰Po events
- · ²²²Rn decay rate
- mixture of KL-LS and dummy-LS


 by gas-chromatographyricic, Large Liquid Scintillator Detectors 18 Aug. 25






Higher energy resolution for reducing 2ν BG







KamLAND2-Zen

Winston cone

light collection ×1.8

high q.e. PMT 17" $\phi \rightarrow 20$ " $\phi \epsilon = 22 \rightarrow 30 + \%$

light collection ×1.9


New LAB LS (better transparency)

light collection ×1.4

expected σ (2.6MeV)= 4% \rightarrow ~2% target sensitivity 20 meV

And more?


Pressurized Xe
Scintillating film
Imaging for β/γaiαic, Large Liqu




Super-KamLAND-Zen in connection with Hyper-Kamiokande

target sensitivity 8 meV


Highlights and Interesting Points from Borexino





- ✓ Similar design, two balloons
- ✓ Outstanding radiopure LS
- ✓ Were stalled for 2 years due to LS leak
- ✓ Incredibly low backgrounds
- ✓ Evidence for pp neutrinos
- ✓ Toward observation of CNO

Convection steers ²¹⁰Po → problem Thermal insulation of Bx







Insulation effect:

Summer 2015


Convection seen in KamLAND too.

SNO+ highlights and Interesting Points

- Converting Water Cherenkov into LS detector huge effort
- Similar concept \rightarrow acrylic sphere instead of balloon
- LLSD 780 tons LAB loaded with Te for NDBD
- New LS and Te purification system, detector refurbishment, leak testing, ropes down...

Status of SNO+ Construction

- SNO+ is fully funded and under construction
- major construction work in the cavity is beginning now
- scintillator purification system ordered, designed and being built; installation in Fall 2011
- □ some "dead" SNO PMTs are being removed, repaired, and replaced
 - it's not planned to repair all dead SNO PMTs; rather, while we have time, we have found many PMTS are easy to repair and easily accessed



SNO+ Status

- Scintillator purification plant installed, commissioning under way
 - First LAB on site in a few months
 - Scintillator fill reginning spring 2017
- In the process of re-filling the detector with ultra-pure water
 - A few leaks in the cavity liner identified and repaired
 - New hold-down system for the acrylic vessel installed and fully tested
 - Making PMT repairs along the way
- Tellurium purification, installation underground beginning later this year
 - Loading system to follow in 2017
 - 1.8 T telluric acid (=1 T Te) stored underground for ~1 year now, 2.0 T telluric acid currently being shipped from supplier





Summary

- Large liquid scintillator detectors are versatile
- Demonstrated simplicity and capacity of LS for loading with different elements
- Very low intrinsic backgrounds of LS, combined with minimal inactive detector material
- Proven purification and suppression of backgrounds in situ
- Self-shielding from external gammas and neutrons: high neutron capture crosssection → excellent neutron veto detectors for DM searches (see DarkSide talk)
- Relatively modest energy resolution affects their discovery potential for NDBD
- Nevertheless, LLSD are an attractive option for low energy rare event searches (few hundred keV to MeV range) since...
 - Low intrinsic background combined with large volume makes them suitable for high sensitivity searches and charting unexplored parameter space
 - Active, high efficiency neutron veto for DM and maybe more than that
- Future detectors show promise of much improved energy resolution

